



ORANJE-NASSAU
ENERGIE



Stringers in Zechstein salt as a drilling risk



Case study Ruby exploration well

Introduction


- Predrill Ruby well assumptions
- Post well analysis of N05-01-S1, N05-01-S2 and N05-01-S3 wells
 - N05-01-S2 experienced a kick in the Z3 Carbonate
- Semi-regional pore pressure model to predict kick magnitude
 - Compaction disequilibrium
 - Additional uplift
- Movable salt to predict overpressure in carbonate stringers
- Seismic modeling to understand pore pressure
 - Can seismic bright spots be used as a predicting tool?
- Approach for future wells
 - Subsurface geometry
 - Drilling technique

Predrill Ruby well assumptions

- Drill through the axis of a syncline
 - Avoid hitting a floater, rather a sinker, to avoid pressures being brought to shallower level
 - Avoid hitting steep dips at Z3 level
 - Smallest change of potential gas column
- In nearby wells (N04-01, N04-02, L08-P01A the Z3 Carbonate is non existent or very thin with poorly developed porosity.






Syncline (Trough) in Z3 Carbonate Mb




Original plans for N05-01 and N05-01-sidetrack were based on the concept of drilling through a trough or syncline in the Z3 Carbonate Mb. In the case of N05-01 this turned out successful: no Z3 Carbonate Mb or floater was seen in the well

Sidetrack Plans




N05-01-S2 Zechstein kick summary


- After drilling through Z3 Main Anhydrite Member, kick in suspected Z3 Carbonate Member
- Flow rate increasing to 1500lpm while shutting in well
- Well did not become statically stable
 - Only dynamically with 1.84sg mud weight and 450gpm circulation
- BHP pressure rises with mud weight increases, chasing a moving target
 - Initial SIDPP: 64 bar with 1.51sg mud, 481 bar at 2813mTVD
 - First well kill: 13 bar with 1.84sg mud, 521 bar at 2813mTVD
 - Second well kill: 5 bar with 1.91sg mud, 532 bar at 2813mTVD
- Tripping in and out not possible
- Decided to cement in BHA



Five step plan to recover from kick




Syncline in Z3 Carbonate Mb, Floater Horizon



However N05-01-S2 unexpectedly found a floater


Trough and Kick Horizon, ST Version R2.0



Section along Yellow Line on previous slide

N05-01-S3 is planned in very close proximity to the N05-01-S1, and parallel to the Syncline


Z3 Carbonate Mb Trough and Kick Horizon, 3D View



For N05-01-S3 we planned to return to the original location of N05-01-S1 to provide (safe) passage through the Z3 Carbonate Mb in the Trough.




Post well analysis

- N05-01-S1 experienced no kick, no Z3 Carbonate, instead ~150m Z3 Main Anhydrite was encountered
- N05-01-S2 experienced a kick of ~1.93 SG EMW after drilling ~60m through Z3 Main Anhydrite
- N05-01-S3 experienced no kick, similar geology with N05-01-S1
 - 25m lateral from original hole



Semi-regional pore pressure model

- Ikona Science estimates a potential overpressure in Zechstein stingers based on the compaction trend of shales and the subsequent uplift of the stringer



Movable salt creating overpressure in carbonate stringers

- Isolated carbonate stringers are being pressurized by movable salts being squeezed into the pores.
 - Ultimately pressure of carbonate stringers cannot exceed SG of the movable salt

Seismic modeling to understand pore pressure

- Can seismic bright spots be used as a predicting tool for overpressured carbonate stringers?


Seismic modeling to understand pore pressure

- Can seismic bright spots be used as a predicting tool for overpressured carbonate stringers?

■ NO

- Reflection of Z3 Main Anhydrite in N04-02 (no Z3 Carbonate) shows higher amplitude than N05-01-S2 (kick)
 - Seismic reflector amplitude brightens at tuning thickness of Z3 Main Anhydrite (20 – 70m)
 - 12% difference in base Z3 Main Anhydrite reflection between N05-01-S2 and N04-02 due to tuning
- Adding Z3 Carbonate to predicting model has the effect of dimming reflection at base Z3 main Anhydrite
- Simulating overpressured pores the acoustic velocity might increase (water compressibility ↑, elastic properties minerals ↓, gas saturation equilibrium ↑ ↓, diagenesis ↓)
 - Increasing in V_p/V_s (VES) from 40 – 140 bars gives a 10% increase in amplitude at base Z3 Main Anhydrite
- Tuning effect is probable cause for high amplitudes at Z3 Main Anhydrite (main well, sidetrack and N04-02)
- Slight increase of reflectivity below Z3 Main Anhydrite might represent overpressure (avoid).

Seismic comparison with N04-02




The reflections at the top and base main anhydrite are generally bright

Zechstein well ties

hansa

HYDROCARBONS




The amplitude of the top and base main anhydrite reflection is much higher in N04-02.

Scenario I - Wedge based on Interpolated well data


hansa

HYDROCARBONS



Thinning of the main anhydrite in N05-01 S1 results in a 35% increase in amplitude due to tuning



Amplitude Response of blocky model using Ricker and Extracted Wavelets



12% difference in base main anhydrite reflection between N05-01 and N04-02 due to tuning

Wedge Models Comparing effects of Carbonate member

hansa
HYDROCARBONS



- Adding in the Platten Dolomite has the effect of dimming the reflection at the base of the main anhydrite
- Tuning effects are very similar in both models

Ways that Pore Pressure Impacts Velocities

The logo for Hansa Hydrocarbons, featuring the word "hansa" in a white, lowercase, sans-serif font on a dark red, triangular background that tapers to the right.



HYDROCARBONS

- Increasing pore pressure softens the elastic mineral frame by opening cracks and flaws, tending to lower velocities.
- Increasing pore pressure tends to make the pore fluid or gas less compressible, tending to increase velocities.
- Changing pore pressure can change the saturation as gas goes in and out of solution. Velocities can be sensitive to saturation.
- High pore pressure persisting over long periods of time can inhibit diagenesis and preserve porosity, tending to keep velocities low.

Slab Model - Z3 Grey salt member overlying Z2 Strassfurt Formation

transa
HYDROCARBONS


Six VES location were sampled and the resulting V_p , V_s values were used to create the blocky model below



Slab Model - Z3 Grey salt member overlying Z2 Stassfurt Formation

hansa

HYDROCARBONS




- ★ Typical effective stress at N05-01 well- 140bars
- ★ Calculated effective stress of kick 41.2 bars

A change in VES from 40- 140 Bars gives a circa 10% increase in amplitude on the Z3 anhydrite /Grey clay interface.



N07-04 Planning

N07-04 (Tanzaniet)



N07-04 Zechstein strategy development

- | | |
|---------------------------------|--------------------|
| ■ 13 3/8" shoe in top Zechstein | 2136mMD (2100mTVD) |
|---------------------------------|--------------------|

- | | |
|----------------------------|--------------------|
| ■ Z3 Main Anhydrite Member | 2620mMD (2565mTVD) |
|----------------------------|--------------------|
- | | |
|---|--------------------|
| ■ Z3 Carbonate Member (potential kick zone), if present | 2658mMD (2602mTVD) |
|---|--------------------|
- | | |
|----------------------------|--------------------|
| ■ Z3 Grey Salt Clay Member | 2668mMD (2612mTVD) |
|----------------------------|--------------------|

- Z3 Carbonate Member is a potential kick zone like in N05-01X, if present at all, and has an expected thickness of 10mTVD. **How to get through this zone?**

- Drill with high (1.9-2sg) mud weight: well will not be statically stable
 - N05-01X showed that the well will not become stable with a higher mud weight
 - Drill with a flowing kick zone: flow too high, too many unknowns, too risky
 - N05-01X kick zone flowed with 1500lpm
 - Overlying Zechstein salt needs 1.5sg mud weight, what happens with unknown weight of brine in hole?
- Any option involving tripping in or out with drill string or casing not possible
- Stopping circulation for connections will accommodate the mud/brine flip and contaminates mud system

- Drilling with casing or liner and cementing it in, eliminates the need to trip
- Drilling with MPD and a continuous flow system allows to drill with 1.50sg mud and keeps the well constantly dynamically stable

N07-04 Step plan visual

13 3/8" shoe installed in top Zechstein. Drill out 13 3/8" shoe and perform FIT (2.04sg).

Drill 12 1/4" hole conventionally into Z3 Main Anhydrite. POOH.

RIH with 650m 9 5/8" liner. Drill with liner through Z3 Carbonate Member (potential kick zone).

1) No kick
POOH liner and continue drilling 12 1/4" hole conventionally

2) Kick encountered
Cement liner in hole, tie back 9 5/8" to well head. Continue down scaled.

