


Practical considerations on the abandonment of a cavern field

Matthias Brandt, IfG Leipzig




INSTITUT FÜR
GEBIRGSMECHANIK
GMBH







Geological Map from:

Geotektonischer Atlas von Nordwest-Deutschland, (BGR, 1999)







Cavern T1

Volume: 1,35 Mio. m³

Cavern T3


Volume: ca. 0,08 Mio. m³

Cavern T5

Volume: 1,54 Mio. m³

Cavern T6

Volume: 1,053 Mio. m³



Model layout: **2D axissymmetric, type caverns**

Triaxial Short Term Strength:
$$(\sigma_{vM})_{max} = \sigma_D + \frac{\sigma_{MAX} - \sigma_D}{\sigma_3 + \sigma_\phi} \cdot \sigma_3$$

Site specific parameters: $\sigma_D = 24 \text{ MPa}$ (uniaxial strength) $\sigma_{MAX} = 63 \text{ MPa}$ $\sigma_\phi = 5 \text{ MPa}$

Utilization factor:
$$\eta = \frac{\sigma_{vM}}{(\sigma_{vM})_{max}}$$


Stationary creep:
$$\dot{\epsilon}_C = A \cdot \sigma^n \quad A = A_0 \cdot \exp\left(-\frac{Q}{R \cdot T}\right)$$




single exponent power law



$A_0 = 2,7 \text{ d}^{-1}$ (T1) $4,5 \text{ d}^{-1}$ (T2) $n = 5$ and $Q/R = 6519 \text{ K}$

Darcy flow approximation:
$$\frac{\Delta V}{\Delta t} = \frac{K A_E}{\eta I_E} \Delta p$$


Constant permeability









Pressure at the cavern base (1270 m) after sealing




Pressure at the cavern roof (670 m) after sealing




Volume convergence





Surface subsidence



Brine permeation







Model layout: field scale 3D model with detailed caverns

Triaxial Strength:
$$(\sigma_{vM})_{max} = \sigma_D + \frac{\sigma_{MAX} - \sigma_D}{\sigma_3 + \sigma_\phi} \cdot \sigma_3$$

Strength depends on damage evolution

Creep modelling:
$$\dot{\epsilon}_C = A_1 \cdot \exp\left(-\frac{Q_1}{R \cdot T}\right) \cdot \sigma^{n_1} + A_2 \cdot \exp\left(-\frac{Q_2}{R \cdot T}\right) \cdot \sigma^{n_2}$$

multi component power law

transient creep


Darcy flow approximation:

$$\frac{\Delta V}{\Delta t} = \frac{K(\sigma, p)}{\eta} \frac{A_E}{I_E} \Delta p$$


Stress- and pressure dependent permeability

Thermal effects included

[d¹]





Different published permeability relations for the increase in permeability of rock salt when fluid pressure exceeds the least compressive stress component (Duquesnoy, 2017).




Laboratory results of hydro-mechanically coupled permeability measurements performed at the IfG for different fluid pressures in relation to the minor principal stress

Sealing of caverns → pressure buildup due to convergence




Brine pressure stabilizes cavern contour

Brine pressure reduced convergence and subsidence



Brine permeation into the salt only around contour



Thank you for your attention!



INSTITUT FÜR
GEBIRGSMECHANIK
GMBH

